

PRODUCT DATA SHEET

Avery Dennison® DOL 6000 Floor Marking

Issued: 12/2020

Introduction

Avery Dennison DOL 6000 is a transparent textured overlaminate designed to protect media on the **indoor** floor applications, ensuring robust full color graphics and excellent slip and wear resistance during its functional life. It is compatible with Avery Dennison MPI 2001 and MPI 2002.

Conversion

For processing tips and reference guides please refer to 5.7 Technical Bulletin: Recommendations for conversion, application and use of Avery Dennison Floor Marking.

When laminating over printed images, the used inks/toners should be thoroughly dry and free of (silicone) additives that might reduce/prevent proper adhesion of Avery Dennison DOL 6000.

Recommendations

- » Indoor retail floor advertising and decoration
- » Office interior decoration (up to 9 months)
- » Exhibition indoor floor graphics

Features

- » Overlamination film with matt textured surface for indoor floor graphics protection
- » Extended life span up to 9 months durability in combination with MPI 2001, MPI 2002 (**for indoor use**)
- » Excellent slip and wear resistance, certified according to DIN norm
- » Fire classification rating available
- » Easy to handle film providing robust full color graphics in combination with MPI 2001, MPI 2002
- » Slip Resistance Classification R10 according to DIN 51130:2014



Face Film

210 micron, transparent matt textured vinyl overlamination film



Adhesive

Clear permanent acrylic based adhesive



Backing

Clay coated kraft paper, 95 g/m2



Durability

9 months



Shelf Life

2 years

Physical Characteristics

	Test method ¹	Results
Product		
Caliper, facefilm (micron)	ISO 534	210
Caliper, facefilm + adhesive (micron)	ISO 534	245
Dimensional stability (mm max.)	FINAT FTM 14	0.4
Shelf life (years)	Stored at 22° C/50-55 % RH	2
Durability ² (months), indoors only	Vertical exposure	9
Fire Classification Rating	EN 13501-1	B _{fl} -s1
Slip Resistance Rating	DIN 51130:2014	R10
Adhesive		
Adhesion, initial (N/m)	FINAT FTM-1, stainless steel	360
Adhesion, after 24 hours (N/m)	FINAT FTM-1, stainless steel	480
Temperature range		
Application temperature (min °C)		see TB 5.4
Service temperature (°C to +°C)		0 - +40
Chemical properties³		
Chemical resistance	Mild acids	No effect
Solvent resistance	Mild alkalis	No effect
Solvent resistance	Applied to aluminium	No effect exposed to: oils, greases, aliphatic solvents, motor oils, heptane, kerosene and JP-4 fuel.

Important

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

1) Test methods: More information about our test methods can be found on our website.

2) Durability: The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

3) Prolonged immersion in gasoline and similar fluids is not recommended.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>.

Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

© 2021 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.