HP Latex FS50 W Printer





STUNNING—Quality that drives high margins	SCALABLE-As your business grows	SUSTAINABLE—With environmental certifications
 You can grow into higher-margin jobs with up to 30% wider gamut¹ at high speed-preserving media 	 Integrate future enhancements with a scalable platform ready to meet evolving business needs. 	 This printer is built to last⁶ thanks to its scalable design.
 gloss, feel. Stand out with a wide range of signage and décor applications-thin films, vinyl, odorless² backlit 	 Meet tight turnarounds with speeds up to 89 m² (958 ft²) per hour⁴ today. Minimize ink waste and streamline your workflow 	 Create a comfortable workspace–water-based inks enable odorless prints² and no hazardous air pollutants⁷.
 textiles. Consistent color and quality configurations across your global fleet with HP Configuration Center³. 	 with auto printhead cleaning and an intuitive interface. Print remotely and monitor fleet with HP Live Production included in HP Professional Print Service Plan⁵. 	 Stand out with an offering that meets environmental certifications like UL ECOLOGO^{#8} and UL GREENGUARD⁹.
		 Contribute to the circular economy with HP Planet Partners¹⁰ and PVC alternative media profile database¹¹.

Sustainability in action

Messaging Footnotes

¹Based on testing commissioned by HP and performed by Venture Electronics Spain, comparing the gamuts of HP Latex Gen 4 inks with those of leading competitive alternatives using UV technology. Test performed under the same conditions in all printers measuring the ECi2002 target with the FD-9 spectrophotometer from Konica Minolta. ²Based on testing commissioned by HP and performed by Odournet and applicable to HP Latex Inks. Testing conducted according to VDI Guideline 3882 where 832 and 873 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. ³HP Learn's free training content, HP Print Beat remote monitoring of production and analytics, HP PrintOS Mobile, and HP Configuration Center are available free of charge for all HP printeds with HP PrintOS. Requires an HP PrintOS account, Internet connection, and connected in Internet-capable dedvice. For more information, see http://www.printos.com. ⁴Based on internal HP testing. Outdoor mode 3-pass, 6-color, 90%. While CMYK and Optimizer are duplicated with symmetrical double printheads, Overcoat, Light Magenta and Light Cyan rely on single printheads.

⁵HP PrintOS Live Production is available for subscribers of the HP Professional Print Services Plus Plan. Please consult your HP representative for information about availability and/or geographic coverage. Requires an HP PrintOS account, Internet connection, and

**H2 PrintOS Live Production is available for subscribers of the HP Professional Print Services Public Plan Please consult your HP representative for information about availability and/or geographic coverage. Requires an HP PrintOS account, internet connection, and connected internet-coapable device. For more information, see http://www.printos.com.
 ⁶Based on HP Large Format supplies Long Term Plan, at least 70% of printers installed, from the previous generation, are still in use in 2024. And on average printers in use are 6-7 years old and at least 50% of printers are > 6 years old.
 ⁷H2 Lates links were tested for Hazardous & Air Polutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.
 ⁸ UL ECOLOGO* Certified HP 832, HP 872, HP 873, and 882, FS50 and FS60 printer series Latex links meet a range of stringent human health and environmental considerations. For certifications, see http://www.ul.com/gg.
 ⁹ Applicable to HP Latex links. UL GREENGUARD Gold Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. Unrestricted room size–full decorated room; 334 m² (800 ft) in a cleastroom environment, FO more information, visit http://www.ulcom/ge. For certifications, see http://www.greenguard.org.
 ¹⁰ Visit http://www.greenguard.org. For ce

local waste authorities on appropriate disposal. ¹¹HP applications experts have evaluated the catalog of media listed in the HP Media Locator based on internal criteria to identify those that provide alternative solutions with certain environmental benefits compared to the typical media within the same application type. The information in media locator is provided by the media substrate vendors. HP is not responsible for the veracity of the information from third-party companies published on the HP website. See http://www.hp.com/go/mediasolutionslocator.

For more information, please visit http://www.hp.com/go/latex-fs50-series Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/



Technical specifications

Print		Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas,
Print speed	1302 ft²/hr (2-pass); 958 ft²/hr (3-pass); 743 ft²/hr (4-pass); 527 ft²/hr (6-		synthetics, fabrics, mesh, textiles ¹
pass); 409 ft²/hr (8 (60%); 183 ft²/hr - V	pass); 409 ft²/hr (8-pass); 312 ft²/hr (10-pass); 581 ft²/hr - White Spot	Connectivity	
	(60%); 183 ft²/hr - White Overflood (100%); 108 ft²/hr - 3 Layers (60%); 36 ft²/hr - 5 Layers	Interfaces	Intel I210-T1 Gigabit Ethernet (1000Base-T)
Print resolution	Up to 1200 x 1200 dpi	Dimensions (W x D x H)	
Technology	HP Latex Printing Technologies	Printer	228 x 54 x 66 in
Ink types	Water-based HP Latex Inks	Shipping	231 x 71 x 75 in
Print Cartridges/Bottle,		Weight	
Number	9 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat, white)	Printer	2916 lb
Print cartridge/bottle	5 L (color) upgradeable to 10 L with B3SG0A; 3L (white)	Shipping	4630 lb
volume delivered		Included	
Printheads	9 (6 HP Latex Universal, 2 HP Latex Optimizer, 1 HP Latex White)	What's in the box	HP Latex FS50 W Printer, printheads, 126-in spindles (x2), HP Internal
Long-term print-to-print repeatability	Maximum color difference (95% of colors) ≤ 2 dE2000		Print Server, touch monitor, documentation software, user manual, media edge holders, Original HP sample media, cleaning supplies, pneumatic gun, User Maintenance Kit
Media		Environmental ranges	prodriado gar, osor maintenance na
Applications	Exhibition and event graphics; Decoration; Displays; Exterior signage;	Operating temperature	59 to 86°F
	Indoor posters; Banners; Light boxes - film; POP/POS; Textile; Vehicle graphics; Wallpaper; Window graphics	Operating humidity	20 to 70% RH (non-condensing)
Handling			
	(optional), ink collector (optional)	Sound pressure	Printing: 71 dB(A) (operating), 58 dB(A) (idle)
Maximum media width	126 in (single roll); 2 x 63 in (optional dual roll); 2 x 60 in (optional jumbo dual roll)	Power	
Media rolls	1 (2 with optional dual roll kit)	Consumption	12-13 kW (printing), 510 W (ready), 110 W (low power mode), 100 W (shutdown)
Roll size	Up to 126 in (single roll); Up to 2 x 63 in (optional dual roll); Up to 2 x 60 in (optional jumbo dual roll)	Requirements	Input voltage 200-240/380-415 V Delta/Wye three-phase and PE; 50/6 Hz; 56/35 A
Maximum roll weight			12,00,007
	x 155 lb (with optional dual roll kit); Up to 2 x 440 lb (with optional jumbo dual roll kit)	Certification Safety	IEC 623681 compliant; United States and Canada (CSA listed); EU (M
Maximum roll diameter	11.8 in (15.75 in with optional diverter roller)		compliant, EN60204-1, EN12100, EN13849-1, EN1010-1); Ukraine (UA)
Thickness	Up to 0.015 in (default); up to 0.08 in (with custom carriage height setting)	Electromagnetic	Compliant with Class A requirements: USA (FCC rules), Canada (ICES EU (EMC Directive), Australia (ACMA), New Zealand (RSM), Korea (KCC
	oorang)	Environmental	WEEE, RoHS (EU, China, Ukraine), REACH, CE marking compliant

Ordering	information
----------	-------------

Product		Us
9T923C Accessories	HP Latex FS50 W Printer	cc
Accessories		Or
3Y0K4A	HP Latex 2700/FS Ink Collector Kit	inv
474X9A	HP Latex 2700/FS Jumbo Dual Roll Kit	htt
474Y0A	HP Latex 2700/FS Ink Collector Foams Kit	Or
4J0X0A	HP 126-in Dual Roll Kit	HP
4R4W4A	HP 126-in Spindle	HF
4R4W5A	HP Latex 126-in Roll Freefall Kit	HF
4R4W7A	HP 126-in Diverter Roller	HF
55P20A	HP Latex 2700/FS Standard Uptime Kit	Fo
55P22A 79D06A	HP Latex 2700/FS User Maintenance Kit HP Latex 2700/FS Edge Holder Kit	Se
B3SG0A	HP Latex FS Series High Capacity Ink Upg	<u></u>
G1K80B	HP 126-in Dual Roll Spindle	U9
L2E28A	HP Latex Jumbo Dual Roll Split Spindles	Wo
M2J33A	HP Latex In-Line Slitters	U9
T4E58B	HP Latex Media Saver Kit	Wa U9
	rinting supplies	Wa
G0Z21A	HP 886 White Latex Printhead	U9
G0Z22A	HP 886 Optimizer Latex Printhead	Wo
G0Z24A	HP 886 Latex Printhead	HP
G0Z28A	HP 883 5-liter Cyan Latex Ink Cartridge	Fo
G0Z29A	HP 883 5-liter Magenta Latex Ink Cartridge	
G0Z30A	HP 883 5-liter Yellow Latex Ink Cartridge	
G0Z31A	HP 883 5-liter Black Latex Ink Cartridge	
G0Z32A	HP 883 5-liter Light Cyan Latex Ink Cartridge	
G0Z33A	HP 883 5-liter Light Magenta Latex Ink Cartridge	
G0Z34A	HP 883 5-liter Optimizer Latex Ink Cartridge	
G0Z35A	HP 883 5-liter Overcoat Latex Ink Cartridge	
G0Z44A	HP 883 3-liter White Latex Ink Cartridge	

Connectivity	
Interfaces	Intel I210-T1 Gigabit Ethernet (1000Base-T)
Dimensions (W x D x H)	
Printer	228 x 54 x 66 in
Shipping	231 x 71 x 75 in
Weight	
Printer	2916 lb
Shipping	4630 lb
Included	
What's in the box	HP Latex FS50 W Printer, printheads, 126-in spindles (x2), HP Internal Print Server, touch monitor, documentation software, user manual, media edge holders, Original HP sample media, cleaning supplies, pneumatic gun, User Maintenance Kit
Environmental ranges	
Operating temperature	59 to 86°F
Operating humidity	20 to 70% RH (non-condensing)
Acoustics	
Sound pressure	Printing: 71 dB(A) (operating), 58 dB(A) (idle)
Power	
Consumption	12-13 kW (printing), 510 W (ready), 110 W (low power mode), 100 W (shutdown)
Requirements	Input voltage 200-240/380-415 V Delta/Wye three-phase and PE; 50/60 Hz; 56/35 A
Certification	
Safety	IEC 62368-1 compliant; United States and Canada (CSA listed); EU (MD compliant, EN60204-1, EN12100, EN13849-1, EN1010-1); Ukraine (UA)
Electromagnetic	Compliant with Class A requirements: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), Korea (KCC)
Environmental	WEEE, RoHS (EU, China, Ukraine), REACH, CE marking compliant
Warranty	One-year limited hardware warranty

Use Original HP inks and printheads, and HP large format printing materials, to experience tent high quality and reliable performance that enable less downtime. These critical nents are designed and engineered together as an optimized printing system, and al HP inks are designed to maximize the life of HP printheads. Protect your HP printer nent by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks al HP large format printing materials

oto-realistic Poster Paper timal Gloss Air GRP (REACH Compliant²) novable Adhesive Fabric (REACH Compliant²) oz Prime Double-sided Blockout Banner (REACH Compliant²) entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com. e and Support

E HP 2 year Plus Service Plan Hardware Support w/DMR for HP Latex FS50 White (In ntv)

E HP 3 year Plus Service Plan Hardware Support w/DMR for HP Latex FS50 White (In ntv)

//E HP 4 year Plus Service Plan Hardware Support w/DMR for HP Latex FS50 White (In nty)

NE HP 5 year Plus Service Plan Hardware Support w/DMR for HP Latex FS50 White (In nty)

pport Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). pre information, please visit http://www.hp.com/go/cpc

Specification Footnotes

¹Performance may vary depending on media–for more information, see http://www.hp.com/go/mediasolutionslocator . For best results, use textiles that do not stretch. The optional ink collector

is required for porous textiles. ² This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. February 2025