

Jetpro Easy Cling Window Film Clear / 140gsm **SM-6063-1370-50UVEL**

Jetpro Easy Cling Window Clear PET film is a removable, recyclable and environmental friendly product designed for window and smooth surface application. This series product is a premium printing media with innovative cling technology for graphics, printing and sign markets. It doesn't rely on chemical adhesion, magnetic force or static, it can cling onto glass, and other smooth surface easily by using vacuum force. So it is low-tack and will not leave adhesive on applying surface.

Applications

Suitable for perfectly smooth substrates like window glass. This easy to remove film ensures no residual at all even after a very long application period as well as no damage to the application surface.

Installation and handling

- Due to different applying surface and environment, we can not guarantee the material will work on every condition. Please always test on applying surface before large scale usage.
- The application area should be clean and free of dirt or oil.
- Keep the film flat during application, crease and curing will affect the adhesion persistence.
- Using water to assist applying the material is recommended. To avoid bubble generated from remaining water between film and window, press hard to remove all water in between film and window. Do not leave any water inside film.

Specifications

Weight: 230gsm

Film weight: 175gsm

Thickness: 180μ

Film thickness: 140μ

Width: 1370mm

Colour: White

Finish: Matt

Liner: Adhesive: Self-vented ultra-low viscosity removable adhesive

Ink compatibility: Latex, Eco-Solvent and UV-Curable

180°Peel Strength: 2~10 g/25mm

Release force: 2~10 g/25mm

Application temperature: Min.-30°C to +130°C

Life expectancy: Up to 2 year

Product Performance and Suitability: We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees. Because of the variety of possible uses, there is no warranty of fitness for a particular purpose. The buyer must test the suitability for each intended application before using. Aarque Group Ltd will not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages. Should any failure to conform to this warranty appear within one year of the initial date of shipment, Aarque Group Ltd shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with Aarque Group Ltd's standards, correct such defects by suitable repair or replacement without charge at Aarque Group Ltd's plant or at the location of the products (at Aarque Group Ltd's election); provided, however, if Aarque Group Ltd determines that repair or replacement is not commercially practical, Aarque Group Ltd shall issue a credit in favour of the buyer in an amount not to exceed the initial purchase price of the product from Aarque Group Ltd