

## Durapro Dot Matt Blockout

DURADOTM1370-50

Durapro Dot is a self-adhesive vinyl with 100-micron monomeric Blockout PVC film, high opacity, removable surface dot matrix adhesive for easy application and repositioning on smooth surfaces, and double-side PE liner of 135gsm, providing great stability to the product, suitable for short term indoor applications

### Specifications

Film Thickness	100 micron Monomeric film
Release Backing Weight	135 gsm
Adhesive Type	Clear Acrylic-base removable dot adhesive easy apply
Finish	White Matt
Release Paper	PE Double side coated
Application Temperature	+10°C
Adhesive Power	After 24h, stainless steel (N/25mm) >4
Shelf Life	24 Months
Storage	Out of direct sunlight at 20°C and 50% relative humidity, The storage area should be dry and clean, stock stored vertically to ensure its quality.
Durability	Up to 12 months.

### Applications

- Designed for indoor smooth surface application, such as glass
- Water application is not recommended
- Surface on which the material will be applied must be carefully cleaned and free from dust or any other contamination that could affect the adhesion of the material.
- Not suitable for floor graphics, low-energy substrates, non-flat surfaces, painted or unpainted drywall, wallpaper, dirty or rough surfaces.
- removing the film from hot surfaces (e.g Shop windows, steel surfaces, etc) is not recommended, as the adhesive may remain on the surface, in such a case, we recommend cooling the surface before removing.
- Surfaces on which the material will be applied should be carefully cleaned and free of dust or any other contamination that may affect adhesion.
- There may be other factors not described that could influence performance during use.
- Before using the film, we recommend that it remains at least 24 hours at the workplace temperature.

**Product Performance and Suitability:** We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees. Because of the variety of possible uses, there is no warranty of fitness for a particular purpose. The buyer must test the suitability for each intended application before using. Aarque Group Ltd will not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages. Should any failure to conform to this warranty appear within one year of the initial date of shipment, Aarque Group Ltd shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with Aarque Group Ltd's standards, correct such defects by suitable repair or replacement without charge at Aarque Group Ltd's plant or at the location of the products (at Aarque Group Ltd's election): provided, however, if Aarque Group Ltd determines that repair or replacement is not commercially practical, Aarque Group Ltd shall issue a credit in favour of the buyer in an amount not to exceed the initial purchase price of the product from Aarque Group Ltd.

### AARQUE GROUP LIMITED

HEAD OFFICE ADDRESS

84 Central Park Drive, Henderson, Auckland

PHONE

0508 22 77 83

WEBSITE

[www.aarque.co.nz](http://www.aarque.co.nz)