PRODUCT SPECIFICATIONS



Clearwipe Whiteboard Laminate / 75 µ

FWBL75M

Clearwipe Whiteboard Laminate is a clear coated polyester pressure sensitive over-laminate film ideal for creating dry-erase surfaces. The hard-coat surface is scratch resistant and does not ghost or create a pearl effect. Can be applied to UV-cured prints, thus eliminating silvering. Can be applied mechanically or wet applied where needed. Recommended for indoor applications onto smooth surfaces.

Features

- No pearling
- No ghosting
- No shrinkage
- Scratch resistant
- Easy to clean

Applications

- ► Permanent markers can be easily wiped off with isopropyl alcohol without damaging the film
- Suitable to be used on top of any smooth printed or unprinted surface with no shrinkage
- ► Can be laminated mechanically or wet applied where needed
- ► Chemical resistance to: Alcohols, dilute acids, dilute alkalis, esters, hydrocarbons, ketones, household cleaning agents
- Schools, Universities
- Bars, Restaurants
- Businesses
- Warehouse, Production
- Healthcare

Specifications

Liner Thickness

Film Type Polyester

Adhesive Permanent Acrylic

Total Thickness 150 μ +/- 8

Total Weight 200gsm +/- 10

Face Film Thickness (no adhesive) $75\mu +/- 2$

Adhesive Peel on Stainless Steel >10 N/25mm

Gloss 20° 90 +/- 2 %

Transmission >90 %

Tensile Strength at break MD 20 TD 28 kgF/mm²

Elongation at break MD 170 TD 110 %

Pencil Hardness 6H

Indoor Durability Up to 12-months

AARQUE GROUP LIMITED 11/02/20

 $50\mu +/-4$

Storage Conditions

Work Room	15°C - 30°C	30% - 65% RH
Usage	10°C - 80°C	10% - 70% RH
Storage	10°C - 20°C	20% - 50% RH

Product Performance and Suitability: We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees. Because of the variety of possible uses, there is no warranty of fitness for a particular purpose. The buyer must test the suitability for each intended application before using. Aarque Group Ltd will not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages. Should any failure to conform to this warranty appear within one year of the initial date of shipment, Aarque Group Ltd shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with Aarque Group Ltd's standards, correct such defects by suitable repair or replacement without charge at Aarque Group Ltd's plant or at the location of the products (at Aarque Group Ltd's election): provided, however, if Aarque Group Ltd determines that repair or replacement is not commercially practical, Aarque Group Ltd shall issue a credit in favour of the buyer in an amount not to exceed the initial purchase price of the product from Aarque Group Ltd.

AARQUE GROUP LIMITED 11/02/20